



## Lightweight

PRODUCT DATA SHEET



### Poplar/Ilomba construction giving significant weight saving and very high quality faces.

Our  Hanson Lightweight Plywood offers stability, ease of cutting and machining and most importantly low density.

 Hanson Lightweight Plywood is available in a number of thicknesses as either Poplar throughout or as an exotic Ilomba faced, Poplar core combi-product. Poplar throughout offers the user a light weight, light colour, high homogeneity with a barely perceptible grain. Whereas the pinker hue of the Ilomba face offers versatility and ideal support for decorative coating materials.

#### Applications

Interior use - general joinery, shop/bar fitting, laminating, veneering, furniture, motorhomes, caravans, portable buildings.

#### SPECIFICATION DETAIL:

Thicknesses (mm)	3mm-25mm (Poplar) ; 3mm -15mm (Ilomba)
Dimensions	2440 x 1220/2500 x 1220/ 3050 x 1220
Average Density	400 Kg/m <sup>3</sup> ± 10%
Manufactured to	EN 636-1
Glue Bond	EN 314-2 Class 1 (Interior)
Formaldehyde Release	Class E1 (Tested to EN 717-2)
Moisture Content	8%-13%
Veneers	High Quality Face and Core
Environmental Certification	PEFC 100%
European Timber Regulation (EUTR) status	Compliant - Sourced within EU
CE Marked	BS EN 13986
Material Safety Data Sheet	Available

#### CONTACT:

Drakes Industrial Estate  
Shay Lane, Halifax  
West Yorkshire  
HX3 6RL

Tel: 01422 330444  
Fax: 01422 330706  
Email: sales@hanson-plywood.co.uk  
www.hanson-plywood.co.uk



For more information visit:  
[www.hanson-plywood.co.uk](http://www.hanson-plywood.co.uk)