

## POPLAR THROUGHOUT











Poplar construction giving significant weight saving and very high quality faces

Poplar throughout offers the user a lightweight, light colour, high homogeneity with a barely perceptible grain. Sustainable and extremely versatile for applications across many industries.

### SPECIFICATION DETAIL

<b>Thickness Range</b>	3mm-30mm
<b>Dimensions (mm)</b>	2440 x 1220 ♦ 2500 x 1220 ♦ 3120 x 1220 ♦ 3050 x 1220
<b>Average Density</b>	400 kg/m <sup>3</sup> ± 10%
<b>Product Classification</b>	EN 636-1
<b>Glue Bond</b>	EN 314-2 Class 1
<b>Formaldehyde Class</b>	E1
<b>Moisture Content</b>	8%-13%
<b>Veneers</b>	High quality face and core
<b>Face Grades</b>	AB/AB, B/BB
<b>Chain of Custody Status</b>	PEFC 100% (FSC® available on request)
<b>EPD (Environmental Product Declaration)</b>	AVAILABLE ( <a href="#">CLICK HERE</a> )
<b>DOP (Declaration of performance)</b>	Available on request
<b>CE Marked</b>	BS EN 13986
<b>Material Safety Data Sheet</b>	Available on request

### APPLICATIONS

-  LAMINATING/VENEERING
-  COMMERCIAL/LEISURE VEHICLES
-  FURNITURE
-  BOAT/YACHT BUILDING
-  EXHIBITION/DISPLAYS
-  SHOP/BAR FITTING
-  CONSTRUCTION/JOINERY
-  LASER CUTTING
-  TOY/MODEL MAKING
-  THEATRE SETS



Talk to a member of our technical team for more information

**Hanson Plywood Limited**  
Drakes Industrial Estate, Shay Lane  
Ovenden, Halifax HX3 6RL

Tel: 01422 330444 Fax: 01422 330706  
Email: [sales@hanson-plywood.co.uk](mailto:sales@hanson-plywood.co.uk)  
[www.hanson-plywood.co.uk](http://www.hanson-plywood.co.uk)



NBS Source



TIMBER DEVELOPMENT UK

