



Interior

Decorative, flexible and versatile thin birch throughout panels



Hanson Special Thin Interior Birch Plywood is a strong yet flexible cross banded plywood produced entirely from Birch veneer with joint free faces.

This plywood is produced using an a interior glue, making it suitable for cutting with a laser.

Being sourced from Finland this product is allowed 100% PEFC accreditation (Programme for the Endorsement of Forest Certification).

## SPECIFICATION DETAIL

**Thickness** 0.4 0.8 1.0 1.5 2.0 3.0 4.0 5.0 6.0 range(mm)

Number of 3 3 3 4 6 8 10 12 veneer layers

1220 x 1220 ♦ 1525 x 1525 ♦ 1550 x 1550 Dimensions (mm)

♦ 1220 x 2440 ♦ 1200 x 2400

**Average Density** Approx. 700 kg/m<sup>3</sup>

EN 636-1 **Product Classification** 

Glue Bond EN 314-2 Class 1

**Face Grade Options** BR/BR

Formaldehyde Class Εī

**Chain of Custody Status** FSC® or PEFC subject to availability

**Further Testing** EN 71-3 (Safety of Toys)

**Material Safety Data Sheet** Available on request

\*Please get in touch with our Sales Team for further information on grading rules

## **APPLICATIONS**



ARCHITECTURAL MODELS

**ENVIRONMENTAL & TECHNICAL** 

**PRODUCT DATA SHEET** 



TOY/MODEL MAKING



**FURNITURE** 



MUSICAL INSTRUMENTS



SHOP/BAR FITTING



JOINERY



ENGINEERING














Talk to a member of our technical team for more information



Drakes Industrial Estate, Shay Lane Ovenden, Halifax HX3 6RL

Tel: 01422 330444 Fax: 01422 330706 Email: sales@hanson-plywood.co.uk





















