SPECIAL COATED

Strong, stable, cross banded, exterior glued birch throughout plywood. Coated with a tough durable phenolic overlay and in most cases acrylic edge sealing

The Phenol coating on our Special Coated Plywood comes in a range of colours and is hot pressed to give both smooth and patterned faces. These can then be used in a wide and varied range of applications where durability, toughness, slip-resistance and resistance to chemicals and other liquids are of the up-most importance.

SPECIFICATION DETAIL

Thickness range(mm)	6 6.5 9 12 15 18 21 24 27
Number of veneer layers	5 5 7 9 11 13 15 17 19
Dimensions (mm)	1220 x 2500 ◆ 1220 x 2440 ◆ 1525 x 3050
Average Density	Approx. 700 kg/m³
Product Classification	EN 636-2
Glue Bond	EN 314-2 Class 3
Formaldehyde Class	E1
Moisture Content	8%-10% at manufacture
Film Patterns	Smooth, Mesh, Diamond, Hexa
Film Colours	Black, dark brown
Core	Uniform and consistent core construction
Chain of Custody Status	FSC® or PEFC subject to availability
DOP (Declaration of Performance)	Available on request
CE Marked	BS EN 13986
Material Safety Data Sheet	Available on request

APPLICATIONS

- VEHICLE BODY BUILDING
- STAGES
- FLIGHT CASES
- HORSEBOXES
- PLATFORMS
- WALKWAYS
- PACKAGING
- FURNITURE



Talk to a member of our technical team for more information

Hanson Plywood Limited
Drakes Industrial Estate, Shay Lane
Ovenden, Halifax HX3 6RL

Tel: 01422 330444
Email: sales@hanson-plywood.co.uk
www.hanson-plywood.co.uk

© HANSON PLYWOOD LIMITED 2023