

POPLAR PLYWOOD



FIRE-DESIGN






Pressure impregnated fire-retardant treated lightweight poplar plywood designed to be used in interior applications


+ Pangua-Fire is a fire retardant plywood classified B-s1,d0 according to European Standards EN 13501-1. An engineered, innovative and modern treated material, to improve safety and reduce the risk of fire. Pangua-Fire meets the new market demands for passive protection against fire of building structures in general, for wall and/or ceiling applications.

SPECIFICATION DETAIL

Thickness Range	6mm-40mm
Dimensions (mm)	2500 x 1220 ♦ 3100 x 1530
Average Density	400 kg/m ³ ± 10%
Product Classification	BS EN 636-1
Formaldehyde Class	E1
Fire Specification	Euro Class B - s1,d0
Face Grade	B/BB
Chain of Custody Status	PEFC 100% (FSC® available on request)
DOP (Declaration of Performance)	Available on request
CE Marked	BS EN 13986
Best Practice Document	AVAILABLE (CLICK TO VIEW)
Material Safety Data Sheet	Available on request

APPLICATIONS

-  EXHIBITION/DISPLAYS
-  COMMERCIAL/LEISURE VEHICLES
-  SHOP/BAR FITTING
-  CONSTRUCTION/JOINERY
-  THEATRE SETS



Talk to a member of our technical team for more information

Hanson Plywood Limited
Drakes Industrial Estate, Shay Lane
Ovenden, Halifax HX3 6RL

Tel: 01422 330444
Email: sales@hanson-plywood.co.uk
www.hanson-plywood.co.uk

