

## Birch Faced

PRODUCT DATA SHEET







Plywood constructed with outer faces of birch veneers with poplar comprising the inner layers.

Our  Hanson Lightweight Panguaneta Plywood offers stability, ease of cutting and combines higher mechanical properties with the benefits of a lightweight panel.

Poplar/birch combi core is available on request. Outer faces are available in both long and cross grain directions. Birch faced poplar plywood is manufactured in accordance with the European and International standards.

### Applications

-  Automotive
-  Furniture and design
-  Shop/Bar fitting
-  Boat/Yacht building
-  Construction, architecture and general joinery

### SPECIFICATION DETAIL:

Thicknesses (mm)	6mm-40mm
Dimensions	2440 x 1220 3050 x 1220
Average Density	400 Kg/m <sup>3</sup> ± 10%
Manufactured to	EN 636-1
Glue Bond	Class 1 (Interior) EN 314-2
Formaldehyde Release	Class E1 (Tested to EN 717-2)
Veneers	High quality face and core
Face Grade	B/BB
Environmental Certification	PEFC (FSC available on request)
European Timber Regulation (EUTR) status	Compliant - Sourced within EU
CE Marked	BS EN 13986
Material Safety Data Sheet	Available

### CONTACT:

Drakes Industrial Estate  
Shay Lane, Halifax  
West Yorkshire  
HX3 6RL

Tel: 01422 330444  
Fax: 01422 330706  
Email: [sales@hanson-plywood.co.uk](mailto:sales@hanson-plywood.co.uk)  
[www.hanson-plywood.co.uk](http://www.hanson-plywood.co.uk)

For more information visit: [www.hanson-plywood.co.uk](http://www.hanson-plywood.co.uk)

