

POPLAR THROUGHOUT











The very highest quality poplar plywood suitable for fine craft work and laser cutting

HL Laser Lite offers the user a light weight, light colour, high homogeneity with a barely perceptible grain. Sustainable and extremely versatile for applications across many industries.

SPECIFICATION DETAIL

Thickness Range	3mm-6mm
Dimensions (mm)	2500 x 1220 (or cut to size)
Average Density	400 kg/m ³ ± 10%
Product Classification	EN 636-1
Glue Bond	EN 314-2 Class 1
Formaldehyde Class	E1
Moisture Content	8%-13%
Veneers	High quality face and core
Face Grades	AB/AB
Chain of Custody Status	PEFC 100% (FSC® available on request)
EPD (Environmental Product Declaration)	AVAILABLE (CLICK HERE)
DOP (Declaration of Performance)	Available on request
CE Marked	BS EN 13986
Material Safety Data Sheet	Available on request

APPLICATIONS

-  LAMINATING/VENEERING
-  COMMERCIAL/LEISURE VEHICLES
-  FURNITURE
-  BOAT/YACHT BUILDING
-  EXHIBITION/DISPLAYS
-  SHOP/BAR FITTING
-  CONSTRUCTION/JOINERY
-  LASER CUTTING
-  TOY/MODEL MAKING
-  THEATRE SETS

