













Our **H** Laser Lite Poplar Plywood offers stability, ease of cutting and machining and most importantly low density.

- Glue bond ideal for laser cutting.
- High uniformity on face and back veneers.
- Available with PEFC™ or FSC® certification.
- Ultra Low Emitting Formaldehyde. (ULEF)

Applications

-  LAMINATING/VENEERING
-  COMMERCIAL/LEISURE VEHICLES
-  FURNITURE
-  BOAT/YACHT BUILDING
-  EXHIBITION/DISPLAYS
-  SHOP/BAR FITTING
-  CONSTRUCTION/JOINERY
-  LASER CUTTING
-  TOY/MODEL MAKING
-  THEATRE SETS

SPECIFICATION DETAIL:

Thicknesses (mm)	3mm, 4mm, 6mm
Dimensions	2500 x 1220mm (or cut to size)
Average Density	400 Kg/m ³ ± 10%
Manufactured to	EN 636-1
Glue Bond	EN 314-2 Class 1 (Interior)
Formaldehyde Release	Class E1 (Tested to EN 717-2)
Moisture Content	8%-13%
Veneers	High Quality Face and Core
Environmental Certification	PEFC 100%
European Timber Regulation (EUTR) status	Compliant – Sourced within EU
CE Marked	BS EN 13986

CONTACT:

Drakes Industrial Estate
 Shay Lane, Halifax
 West Yorkshire
 HX3 6RL

Tel: 01422 330444
 Fax: 01422 330706
 Email: sales@hanson-plywood.co.uk
 www.hanson-plywood.co.uk



For more information visit:
www.hanson-plywood.co.uk

July 2019