

ISP4

LIGHTWEIGHT POPLAR PLYWOOD FOR SHOP/BAR FITTING



Specialist poplar plywood offering a multitude of attributes for the shop/bar fitting industry

A selection of sizes are available with thicknesses ranging from 3.0mm up to 40mm and face grades to suit all applications.

The information illustrated covers the most common specifications used in the industry.

Applicable Products

- ✓ Poplar Throughout
- ✓ Ilomba Twin
- ✓ Fire Retardant
- ✓ Pure Glue Eco Friendly
- ✓ Birch Faced
- ✓ Laser Lite

Applications



SPECIFICATION DETAIL:

Thicknesses (mm)	3mm-40mm
Dimensions (mm)	2440 x 1220, 2500 x 1220, 3050 x 1220, 3120 x 2120
Average density	400 Kg/m ³ ± 10%
Product standard	EN 636-1
Glue bond	EN 314-2 Class 1 (Interior)
Formaldehyde release	Class E1 (tested to EN 717-2)
Moisture content	8%-13%
Veneers	High quality face and core
Environmental certification	PEFC™ 100%
CE marked	BS EN 13986
Material safety data sheet	Available

CONTACT:

Drakes Industrial Estate
Shay Lane, Halifax
West Yorkshire
HX3 6RL

Tel: 01422 330444
Fax: 01422 330706
Email: sales@hanson-plywood.co.uk
www.hanson-plywood.co.uk



For more information visit:
www.hanson-plywood.co.uk

September 2022